

**Description:**

OMNICOTE adheres to metal, plastic and glass. It provides a very tough finish with minimal brush marks. It is very easy to apply and normally provides a very tough finish in just one coat. OMNICOTE also contains a built in rust converter to neutralise rust. Rust is converted to a polymer that is absorbed into the OMNICOTE. Rust is encapsulated into the OMNICOTE and becomes a stable part of the tough coating. OMNICOTE provides ongoing protection against further rusting. This product is an environmentally friendly, water based (quick drying and low odour) high performance coating. Omnicote will also withstand temperatures of up to 250°C once fully cured.

**Area of use:**

Interior, Exterior

**Substrates:**

Metal, Plastic, Glass & Wood

**Packing:**

2.5 litre, 1 litre and 250 ml

**Physical Constants:**

Colour: Black

Finish: Satin

Volume solids: 40%

Theoretical spreading rate: 8 -12 sq. metres per litre

Flash point: N/A

Specific gravity: 1.20

Dry to touch: 30 minutes

Over-coating time: 4-6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

**Application Details:**

Application method: Brush

Thinner: Water

Cleaning of tools: Water

**Surface Condition:**

Ensure surface is free from all flaking material, dust, dirt and grease. Do not apply in temperatures below 8°C.

**Application:**

Apply by brush, Do not overspread, for outside use we recommend applying two coats.

**Warning: Omnicote is not recommended for overcoating with Protectakote.**

*See MSDS for further information. For additional guidance please contact New Venture Product Ltd.*

New Venture Products Ltd Tel: 0845 430 4030 Email: [sales@newventureproducts.co.uk](mailto:sales@newventureproducts.co.uk)

Online Shop: [www.anti-slip-paint.co.uk](http://www.anti-slip-paint.co.uk)