

**Description:**

OMNICOTE adheres to metal, plastic and glass. It provides a very tough finish with minimal brush marks. It is very easy to apply and normally provides a very tough finish in just one coat. OMNICOTE also contains a built in rust converter to neutralise rust. Rust is converted to a polymer that is absorbed into the OMNICOTE. Rust is encapsulated into the OMNICOTE and becomes a stable part of the tough coating. OMNICOTE provides ongoing protection against further rusting. This product is an environmentally friendly, water based (quick drying and low odour) high performance coating.

**Area of use:**

Interior, Exterior

**Substrates:**

Metal, Plastic, Glass & Wood

**Packing:**

1 litre and 250 ml

**Physical Constants:**

Colour: Black

Finish: Satin

Volume solids: 40%

Theoretical spreading rate: 8 -12 sq. metres per litre

Flash point: N/A

Specific gravity: 1.20

Dry to touch: 30 minutes

Over-coating time: 4-6 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

**Application Details:**

Application method: Brush

Thinner: Water

Cleaning of tools: Water

**Surface Condition:**

Ensure surface is free from all flaking material, dust, dirt and grease. Do not apply in temperatures below 8°C.

**Application:**

Apply by brush, Do not overspread, for outside use we recommend applying two coats.

**Warning: Omnicote is not recommended for overcoating with Protectakote.**

*See MSDS for further information. For additional guidance please contact New Venture Product Ltd.*

New Venture Products Ltd Tel: 0845 430 4030 Email: [sales@newventureproducts.co.uk](mailto:sales@newventureproducts.co.uk)

Online Shop: [www.anti-slip-paint.co.uk](http://www.anti-slip-paint.co.uk)