



TECHNICAL SPECIFICATION

Tradesman 2 C/W Twin A1P2 Cartridges

Also Known As Filterjet

Unit Conformity:

Meets the requirements of EN 405.
EC Certificate Number 1198 issued by
BSi Product Certification.

Cartridge Performance:

Offers an assigned protection factor
(APF) of 10 x Workplace Exposure
Limit (WEL) for organic vapours, gases
and very fine dusts, fibres, fumes and
aqueous mists.

Weights: 0.22Kg (approx.)

Materials:

Body: Medical Grade PVC
Fittings: Nylon
Straps: Elastic
Valve Holder ABS
Exhale Valve Latex Rubber
Cartridge Outer Polystyrene
Cartridge Inner Manmade materials

Instructions For Use:

Place the neck strap over the head and
around the neck. Position chin in the
lower part of the respirator and rotate up
onto the face so that the nose is in the
correct position in the respirator. Fasten
the head strap around the head and
tighten straps to give a comfortable fit.
To check for seal, place a piece of
paper, or similar, over the front of the
filters and breathe in sharply, the mask
should be pulled into the face.
If this is not the case adjust the straps
until a seal is created.

**Care must be taken to ensure that the
correct mask and filter type is
selected for the work to be carried
out. If in doubt as to the type required
seek professional advice.**

Cleaning & Maintenance:

Store the respirator in the packaging
provided, out of direct sunlight, away
from chemicals and abrasive
substances. Cleaning the filter does not
extend the life of the respirator. This
product contains no serviceable parts.



Limitations Of Use:

Protection will only be offered if the respirator is fitted correctly.
The respirator must be replaced if:

- **If the 'Use By' date has been reached on the cartridges.**
- **After a maximum of 28 days after opening pack.**
- **If it is removed whilst in the contaminated area.**

The mask, when in contact with the skin may cause allergic
reactions to susceptible individuals. If this occurs leave the
hazard area, remove mask and seek medical advice.

Notes:

- i. **Use in well-ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres.**
- ii. **Ensure good seal around the face is created before entering the hazard area.**
- iii. **The working life of the fitted filters depend on many factors including work rate, airflow and concentration of any contaminant in the atmosphere. As the filters cannot be removed, the respirator should be changed immediately if, a.) Breathing difficulties due to clogging are experienced, b.) Breakthrough of a contaminant is detected by smell, taste or any other means, or c.) The respirator becomes damaged.**
- iv. **This mask is not designed to be worn by people with facial hair or other facial features that may affect seal performance.**

Manufacturing For Safety